

# Water-Resistant Cementitious Skim Coat

CRACK REPAIR & FINISHING

PRODUCT OVERVIEW

Smooth finishing putty for cement-based plaster and concrete. The polymer-modified cementitious formulation is suited to surface levelling, pinhole filling and preparation for decorative paints.

TYPICAL APPLICATIONS

- Fine skim-coating over cement render or fair-faced concrete
- Filling shallow pinholes, scratches and tiny imperfections
- Surface preparation before painting in internal/external environments

REFERENCE TECHNICAL CHARACTERISTICS

|                    |                                                |
|--------------------|------------------------------------------------|
| Appearance:        | White or grey cementitious powder              |
| Layer thickness:   | Up to 3 mm                                     |
| Working time:      | 60 to 90 minutes                               |
| Indicative yield:  | About 22.5 square metres per 25 kg bag at 1 mm |
| Typical packaging: | 5 kg or 25 kg bags                             |

IMPORTANT SELECTION NOTE

Indicative yield is substrate-dependent. Follow the stated preparation, mixing and curing instructions and confirm paint compatibility.

GET SPECIFICATIONS OR REQUEST A QUOTATION

Visit [perfectoqatar.com](http://perfectoqatar.com) / Contact | Quote product reference: PCS-MAT-004